



BACCO FF

Colour: transparent with red plastic spiral.

Temperature range: -10°C + 60°C

hose made with plasticized vinyl compound with spiral, smooth inside, for heavy duty thus flexible. Resistance to loads, atmospheric agents and to a wide range of chemicals. Resistance to hydrolysis.

Tube features: food grade hose wall completely free of phthalates, to eliminate leaching risk of those components into the delivered substances. The hard plastic spiral is as well food grade, making Bacco FF a total food hose. Antistatic version available upon request.

Standards: Food grade according to EU Regulation n° 10/2011 (classes A, B, C).

APPLICATIONS:

ideal solution for suction and delivery of beverages with alcohol concentration up to 20%. Suggested for wines, marcs, liquors and other beverages and food liquids.

See recommendations for technical suitability.

Date: 25th May 2012 - Revision 02, replacing previous editions.

TECHNICAL DATA:

Part Number	Inside Ø	Min. Wall Thickness	Max. Wall Thickness	Weight	Working Pressure	Bursting Pressure	Vacuum	Bending Radius	Roll Length	Volume
	mm	mm	mm	g/m	bar	bar	mH2O	mm	m	m ³
BF 01 020.0 000.0	20	3,2	3,5	310	9	27	10	110	50	0,070
BF 01 025.0 000.0	25	3,3	3,7	400	8	24	10	170	50	0,094
BF 01 030.0 000.0	30	3,5	3,9	500	8	24	10	190	50	0,121
BF 01 032.0 000.0	31,8	3,5	3,9	520	7	21	10	230	50	0,140
BF 01 038.0 000.0	38,1	4,1	4,5	730	7	21	10	260	50	0,191
BF 01 040.0 000.0	40	4,1	4,6	760	7	21	10	270	50	0,208
BF 01 045.0 000.0	45	4,4	4,9	920	7	21	10	310	50	0,242
BF 01 050.0 000.0	50	4,7	5,3	1100	6	18	10	350	50	0,315
BF 01 052.0 000.0	50,8	4,7	5,3	1120	6	18	10	350	50	0,319
BF 01 060.0 000.0	60	5,2	5,8	1470	6	18	10	415	50	0,469
BF 01 063.0 000.0	63,5	5,5	6,1	1630	6	18	10	440	50	0,511
BF 01 070.0 000.0	70	5,6	6,3	1800	5	15	10	480	50	0,611
BF 01 076.0 000.0	76,2	5,7	6,3	1960	5	15	10	525	50	0,657
BF 01 080.0 000.0	80	6,1	6,8	2200	5	15	10	555	30	0,550
BF 01 090.0 000.0	90	6,4	7,1	2610	5	15	10	630	30	0,631
BF 01 100.0 000.0	100	7,3	8,1	3310	5	15	9	695	30	0,784
BF 01 102.0 000.0	102	7,3	8,1	3360	5	15	9	695	30	0,797
BF 01 120.0 000.0	120	7,8	8,6	4210	4	12	9	900	30	1,162
BF 01 127.0 000.0	127	7,7	8,6	4410	4	12	9	1000	30	1,250



