



## EOLO PU FOOD

**Colour:** transparent with ivory spiral.

**Temperature range:** -40°C+80°C -40°F + 176°F

**Features:** ether based PU wall , food grade, with antishock rigid PVC spiral. Smooth inside, corrugated outside. Light, extremely resistant to abrasion and flexion, this hose features high mechanical properties. Resistant to many chemicals.

Foodgrade according to FDA Reg. CFR 21 -Item 177.2600 (acquous and fatty food) and to EU Regulation 10/2011, (classes A,B,C,D2- for further details see the Information Sheet).

### Food grade Spiral

### APPLICATIONS:

light suction of food

**TECHNICAL DATA:**

Part Number	Inside Ø	Min. Wall Thickness	Max. Wall Thickness	Weight	Vacuum	Bending	Roll Length	Volume
	mm	mm	mm	g/m	m H2O	mm	m	m³
EU 01 020.0 000.0	20	0,4	2,5	110	2,5	25	20	0,028
EU 01 025.0 000.0	25	0,4	2,6	150	2,5	30	20	0,035
EU 01 030.0 000.0	30	0,4	2,6	160	2,5	35	20	0,049
EU 01 032.0 000.0	31,8	0,4	2,6	180	2	35	20	0,051
EU 01 035.0 000.0	35	0,5	2,7	200	2	45	20	0,059
EU 01 038.0 000.0	38,1	0,5	2,8	220	2	50	20	0,068
EU 01 040.0 000.0	40	0,5	2,8	230	2	60	20	0,071
EU 01 045.0 000.0	45	0,5	2,9	270	2	65	20	0,083
EU 01 052.0 000.0	50,8	0,5	3,2	320	2	70	20	0,104
EU 01 055.0 000.0	55	0,5	3,4	400	2	75	20	0,119
EU 01 060.0 000.00	60	0,5	3,6	470	1,6	80	20	0,170
EU 01 063.0 000.0	63,5	0,5	3,6	510	1,6	80	20	0,180
EU 01 065.0 000.0	65	0,5	3,6	520	1,6	90	20	0,191
EU 01 070.0 000.0	70	0,6	3,9	560	1,6	95	30	0,293
EU 01 076.0 000.0	76,2	0,6	3,9	600	1,6	100	30	0,328
EU 01 080.0 000.0	80	0,6	4,2	650	1,6	110	30	0,357
EU 01 090.0 000.0	90	0,6	4,3	750	1,4	125	30	0,547
EU 01 100.0 000.0	100	0,6	4,4	820	1,3	140	30	0,640
EU 01 102.0 000.0	102	0,6	4,4	830	1,3	140	30	0,652
EU 01 110.0 000.0	110	0,6	4,7	950	1,2	150	30	0,743
EU 01 120.0 000.0	120	0,6	5,0	1100	1	160	30	0,831
EU 01 127.0 000.0	127	0,6	5,0	1150	1	170	30	0,900
EU 01 130.0 000.0	130	0,7	5,3	1300	0,9	170	20	0,780
EU 01 140.0 000.0	140	0,7	5,3	1430	0,9	180	20	0,860
EU 01 150.0 000.0	151,5	0,7	5,3	1500	0,8	200	20	0,953
EU 01 160.0 000.0	160	0,7	6,7	1940	0,7	220	20	1,049
EU 01 180.0 000.0	180	0,7	6,7	2140	0,4	250	20	1,236
EU 01 200.0 000.0	200	0,7	6,7	2300	0,4	260	20	1,440
EU 01 250.0 000.0	250	0,8	7,5	3400	0,4	300	10	0,952
EU 01 300.0 000.0	300	0,8	7,7	4100	0,3	350	10	1,419

