



SAFETY DATA SHEET
DRY PTFE SPRAY

Page: 1

Compilation date: 04/05/2014

Revision No: 6

Section 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name: DRY PTFE SPRAY

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of substance / mixture: Multi-purpose food grade PTFE spray for light, dry lubrication

1.3. Details of the supplier of the safety data sheet

Company name: ROCOL

ROCOL House

Swillington

Leeds

West Yorkshire

LS26 8BS

ENGLAND

Tel: +44 (0) 113 232 2700

Fax: +44 (0) 113 232 2740

Email: customer-service@rocol.com

1.4. Emergency telephone number

Emergency tel: +44 (0) 113 232 2600

Section 2: Hazards identification

2.1. Classification of the substance or mixture

Classification under CHIP: F+: R12; -: R67

Most important adverse effects: Extremely flammable. Vapours may cause drowsiness and dizziness.

2.2. Label elements

Label elements under CHIP:

Hazard symbols: Extremely flammable.



Risk phrases: R12: Extremely flammable.

R67: Vapours may cause drowsiness and dizziness.

Safety phrases: S38: In case of insufficient ventilation, wear suitable respiratory equipment.

Precautionary phrases: Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use.

Do not spray on a naked flame or any incandescent material. Keep away from sources of ignition - No smoking. Keep out of the reach of children.

[cont...]

SAFETY DATA SHEET

DRY PTFE SPRAY

Page: 2

2.3. Other hazards

Other hazards: Combustion may also generate: decomposition products that may lead to polymer fume fever (24 - 48 hr influenza-like symptoms).

PBT: This product is not identified as a PBT/vPvB substance.

Section 3: Composition/information on ingredients

3.2. Mixtures

Hazardous ingredients:

HYDROCARBON AEROSOL PROPELLANT (<0.1% 1,3-BUTADIENE)

| EINECS | CAS | CHIP Classification | CLP Classification | Percent |
|-----------|------------|---|-------------------------------------|---------|
| 270-704-2 | 68476-85-7 | F+: R12 Substance with a Community workplace exposure limit. | Flam. Gas 1: H220; Press. Gas: H280 | 70-90% |

ACETONE

| | | | | |
|-----------|---------|---------------------------------|--|--------|
| 200-662-2 | 67-64-1 | F: R11; Xi: R36; -: R66; -: R67 | Flam. Liq. 2: H225; Eye Irrit. 2: H319; STOT SE 3: H336; -: EUH066 | 10-30% |
|-----------|---------|---------------------------------|--|--------|

PROPAN-2-OL

| | | | | |
|-----------|---------|-------------------------|---|-------|
| 200-661-7 | 67-63-0 | F: R11; Xi: R36; -: R67 | Flam. Liq. 2: H225; Eye Irrit. 2: H319; STOT SE 3: H336 | 1-10% |
|-----------|---------|-------------------------|---|-------|

Section 4: First aid measures

4.1. Description of first aid measures

Skin contact: Wash immediately with plenty of soap and water.

Eye contact: Bathe the eye with running water for 15 minutes. Consult a doctor.

Ingestion: Wash out mouth with water. Do not induce vomiting. Consult a doctor.

Inhalation: Remove casualty from exposure ensuring one's own safety whilst doing so. Consult a doctor.

4.2. Most important symptoms and effects, both acute and delayed

Skin contact: There may be irritation and redness at the site of contact.

Eye contact: There may be irritation and redness. The eyes may water profusely.

Ingestion: There may be soreness and redness of the mouth and throat. May cause dizziness.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest. Drowsiness or mental confusion may occur.

4.3. Indication of any immediate medical attention and special treatment needed

Section 5: Fire-fighting measures

[cont...]

SAFETY DATA SHEET

DRY PTFE SPRAY

Page: 3

5.1. Extinguishing media

Extinguishing media: Do not use water. Alcohol resistant foam. Carbon dioxide. Dry chemical powder. Use water spray to cool containers.

5.2. Special hazards arising from the substance or mixture

Exposure hazards: Extremely flammable. Forms explosive air-vapour mixture. In combustion emits toxic fumes of carbon dioxide / carbon monoxide.

5.3. Advice for fire-fighters

Advice for fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

Section 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Refer to section 8 of SDS for personal protection details. Eliminate all sources of ignition.

6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers.

6.3. Methods and material for containment and cleaning up

Clean-up procedures: Do not use equipment in clean-up procedure which may produce sparks. Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for disposal by an appropriate method.

6.4. Reference to other sections

Section 7: Handling and storage

7.1. Precautions for safe handling

Handling requirements: Ensure there is sufficient ventilation of the area. Do not handle in a confined space. Smoking is forbidden.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Store in cool, well ventilated area. Keep away from sources of ignition. Keep away from direct sunlight. Ensure lighting and electrical equipment are not a source of ignition.

Suitable packaging: Must only be kept in original packaging.

7.3. Specific end use(s)

Section 8: Exposure controls/personal protection

8.1. Control parameters

[cont...]

SAFETY DATA SHEET

DRY PTFE SPRAY

Page: 4

Hazardous ingredients:

HYDROCARBON AEROSOL PROPELLANT (<0.1% 1,3-BUTADIENE)

Workplace exposure limits:

Respirable dust

| State | 8 hour TWA | 15 min. STEL | 8 hour TWA | 15 min. STEL |
|-------|-------------------|-------------------|------------|--------------|
| UK | 1000ppm 1750mg/m3 | 1250ppm 2180mg/m3 | - | - |

ACETONE

| | | | | |
|----|------------|------------|---|---|
| UK | 1210 mg/m3 | 3620 mg/m3 | - | - |
|----|------------|------------|---|---|

PROPAN-2-OL

| | | | | |
|----|--------------------|---------------------|---|---|
| UK | 400 ppm, 999 mg/m3 | 500 ppm, 1250 mg/m3 | - | - |
|----|--------------------|---------------------|---|---|

DNEL/PNEC Values

DNEL / PNEC No data available.

8.2. Exposure controls

Engineering measures: Ensure there is sufficient ventilation of the area. Ensure lighting and electrical equipment are not a source of ignition.

Respiratory protection: Respiratory protection not normally required.

Hand protection: Protective gloves.

Eye protection: Safety glasses with side-shields.

Skin protection: Protective clothing.

Section 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

State: Aerosol

Colour: White

Odour: Sweet-smelling

Evaporation rate: Fast

Oxidising: Non-oxidising (by EC criteria)

Solubility in water: Soluble

Viscosity: Non-viscous

Boiling point/range°C: <0

Melting point/range°C: <-130

Flammability limits %: lower: 1.8

upper: 9.4

Flash point°C: -104

Autoflammability°C: >200

Vapour pressure: >210

Relative density: <1

9.2. Other information

Other information: No data available.

Section 10: Stability and reactivity

[cont...]

SAFETY DATA SHEET

DRY PTFE SPRAY

Page: 5

10.1. Reactivity

10.2. Chemical stability

Chemical stability: Stable under normal conditions.

10.3. Possibility of hazardous reactions

10.4. Conditions to avoid

Conditions to avoid: Direct sunlight. Heat. Sources of ignition.

10.5. Incompatible materials

Materials to avoid: Strong oxidising agents. Strong reducing agents.

10.6. Hazardous decomposition products

Haz. decomp. products: In combustion emits toxic fumes of carbon dioxide / carbon monoxide. In combustion emits toxic fumes of hydrogen fluoride. Combustion may also generate: decomposition products that may lead to polymer fume fever (24 - 48 hr influenza-like symptoms).

Section 11: Toxicological information

11.1. Information on toxicological effects

Hazardous ingredients:

ACETONE

| | | | | |
|-----|-----|------|------|-------|
| IVN | RAT | LD50 | 5500 | mg/kg |
| ORL | MUS | LD50 | 3 | gm/kg |
| ORL | RAT | LD50 | 5800 | mg/kg |

PROPAN-2-OL

| | | | | |
|-----|-----|------|------|-------|
| IVN | RAT | LD50 | 1088 | mg/kg |
| ORL | MUS | LD50 | 3600 | mg/kg |
| ORL | RAT | LD50 | 5045 | mg/kg |
| SCU | MUS | LDLO | 6 | gm/kg |

Toxicity values: No data available.

Symptoms / routes of exposure

Skin contact: There may be irritation and redness at the site of contact.

Eye contact: There may be irritation and redness. The eyes may water profusely.

Ingestion: There may be soreness and redness of the mouth and throat. May cause dizziness.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest. Drowsiness or mental confusion may occur.

Section 12: Ecological information

[cont...]

SAFETY DATA SHEET

DRY PTFE SPRAY

Page: 6

12.1. Toxicity

Hazardous ingredients:

ACETONE

| | | | |
|---|------|------|------|
| BLUEGILL (<i>Lepomis macrochirus</i>) | LC50 | 8300 | mg/l |
|---|------|------|------|

12.2. Persistence and degradability

Persistence and degradability: Only slightly biodegradable.

12.3. Bioaccumulative potential

Bioaccumulative potential: No bioaccumulation potential.

12.4. Mobility in soil

Mobility: Highly volatile. Soluble in water.

12.5. Results of PBT and vPvB assessment

PBT identification: This product is not identified as a PBT/vPvB substance.

12.6. Other adverse effects

Section 13: Disposal considerations

13.1. Waste treatment methods

Disposal of packaging: Dispose of in a regulated landfill site or other method for hazardous or toxic wastes.

NB: The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

Section 14: Transport information

14.1. UN number

UN number: UN1950

14.2. UN proper shipping name

Shipping name: AEROSOLS, Flammable

14.3. Transport hazard class(es)

Transport class: 2

14.4. Packing group

14.5. Environmental hazards

Environmentally hazardous: No

Marine pollutant: No

14.6. Special precautions for user

Section 15: Regulatory information

[cont...]

SAFETY DATA SHEET

DRY PTFE SPRAY

Page: 7

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.2. Chemical Safety Assessment

Section 16: Other information

Other information

Other information: Contains only FDA listed ingredients. NSF H1 registered.

This safety data sheet is prepared in accordance with Commission Regulation (EU) No 453/2010.

EC Directive 94/1/EC adapting some technicalities of Council Directive 75/324/EEC on the approximation of the laws of Member States relating to aerosol dispensers.

Compiled in accordance with REACH.

Phrases used in s.2 and s.3: EUH066: Repeated exposure may cause skin dryness or cracking.

H220: Extremely flammable gas.

H225: Highly flammable liquid and vapour.

H280: Contains gas under pressure; may explode if heated.

H319: Causes serious eye irritation.

H336: May cause drowsiness or dizziness.

R11: Highly flammable.

R12: Extremely flammable.

R36: Irritating to eyes.

R66: Repeated exposure may cause skin dryness or cracking.

R67: Vapours may cause drowsiness and dizziness.

Legend to abbreviations: PNEC = predicted no effect level

DNEL = derived no effect level

LD50 = median lethal dose

LC50 = median lethal concentration

EC50 = median effective concentration

IC50 = median inhibitory concentration

dw = dry weight

bw = body weight

cc = closed cup

oc = open cup

MUS = mouse

GPG = guinea pig

RBT = rabbit

HAM = hamster

HMN = human

MAM = mammal

PGN = pigeon

[cont...]

SAFETY DATA SHEET

DRY PTFE SPRAY

Page: 8

IVN = intravenous

SCU = subcutaneous

SKN = skin

DRM = dermal

OCC = ocular/corneal

PCP = physico-chemical properties

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.